



ULtra INFILtrant

YOUR WROUGHT/WIRE INFILTRATION SOLUTION.

ultra-infiltrant.com - 1868 Corniche Drive, Zionsville, IN 46077 - 888-ULTRA-55

CERTIFICATE OF COMPLIANCE / STATEMENT OF CONFORMITY

Alloy: Ultra Infiltrant Proprietary Alloy

Patent No: 7341093

Mfg. Date: 6/21/2011 Ship Date: 6/28/2011 Order No: 81985 Item ID: 9232

Heat #: 1) 208924 B398 B399 B400
2)
3)

Elongation: 0 to 0

Cross-Sec: Round Dimension: 0.072 (+) 0.0005 (-) 0.0005

Temper: H66 Tensile PSI: to

Chemistry Specification


Copper:	Remainder		
Zinc:	3.31% - 3.53%	3.42%	Target
Manganese:	0.50% - 0.70%	0.60%	Target
Iron:	1.92% - 2.07%	2.00%	Target
Nickel:	0.20% - 0.20%	0.20%	Target
Tin:	Trace		Maximum
Phosphorous:	Trace		Maximum
Lead:	Trace		Maximum
Aluminum:	Trace		Maximum
Silicon:	Trace		Maximum

Mechanical Data

Diameter: 0.0723 to 0.0724

Meets Chemistry & Mechanical Specification

Ultra Infiltrant Produced in the USA



Paul A. Rivest, CEO