



ULtra INFILtrant

YOUR WROUGHT/WIRE INFILTRATION SOLUTION.

ultra-infiltrant.com - 1868 Corniche Drive, Zionsville, IN 46077 - 888-ULTRA-55

CERTIFICATE OF COMPLIANCE / STATEMENT OF CONFORMITY

Alloy: Ultra Infiltrant Proprietary Alloy

Patent No: 7341093

Mfg. Date: 1/18/2017 Ship Date: 1/19/2017 Order No: 102809 Item ID: 9522

Heat #: 1) 259605 D0840
2)
3)

Elongation: 0 to 0

Cross-Sec: Round Dimension: 0.2280 (+) 0.0030 (-) 0.0030

Temper: O61 Tensile PSI: to

Chemistry Specification

Copper:	Remainder		
Zinc:	3.23% - 3.33%	3.28%	Target
Manganese:	0.60% - 0.80%	0.70%	Target
Iron:	1.89% - 2.03%	1.96%	Target
Nickel:	0.20% - 0.20%	0.20%	Target
Tin:	Trace		Maximum
Phosphorous:	Trace		Maximum
Lead:	Trace		Maximum
Aluminum:	Trace		Maximum
Silicon:	Trace		Maximum

Mechanical Data

Diameter: 0.2258 to 0.2273

Meets Chemistry & Mechanical Specification

Ultra Infiltrant Produced in the USA

Paul A. Rivest, CEO

