



ULtra INFILtrant

YOUR WROUGHT/WIRE INFILTRATION SOLUTION.

ultra-infiltrant.com - 1868 Corniche Drive, Zionsville, IN 46077 - 888-ULTRA-55

CERTIFICATE OF COMPLIANCE / STATEMENT OF CONFORMITY

Alloy: Ultra Infiltrant Proprietary Alloy

Patent No: 7341093

Mfg. Date: 4/12/2016 Ship Date: 5/13/2016 Order No: 99622 Item ID: 9231

Heat #: 1) 251425 D588
2)
3)

Elongation: 0 to 0

Cross-Sec: Round Dimension: 0.0600 (+) 0.0005 (-) 0.0005

Temper: H66 Tensile PSI: to

Chemistry Specification

Copper:	Remainder		
Zinc:	3.41% - 3.41%	3.41%	Target
Manganese:	0.60% - 0.60%	0.60%	Target
Iron:	2.02% - 2.02%	2.02%	Target
Nickel:	0.20% - 0.20%	0.20%	Target
Tin:	Trace		Maximum
Phosphorous:	Trace		Maximum
Lead:	Trace		Maximum
Aluminum:	Trace		Maximum
Silicon:	Trace		Maximum

Mechanical Data

Diameter: 0.0603 to 0.0604

Meets Chemistry & Mechanical Specification

Ultra Infiltrant Produced in the USA

Paul A. Rivest, CEO

